

'No Lost Load' Fork Positioner

Attollo's 'No Lost Load' fork positioners allows fork positioning on existing fork truck carriages or sideshift carriages without increasing the lost load. This fork positioner bolts onto the existing carriage, replacing the original load backrest, making installation quick and straightforward.

The strong robust design with the cylinders mounted above the carriage makes this unit less susceptible to damage than the cheaper hang-on versions with cylinders positioned between the carriage bars. This model is supplied complete with pressure relief valve to improve the service life of the fork positioner and forks and limit down time through accidental misuse.

Hydraulic fork positioning eliminates the manual handling task of moving the forks across the carriage by hand and is increasingly being specified as standard for a productive and safe fleet of forklifts.



Features

- ▶ Adjustment on fork carrier width allows use of most standard ITA forks
- ▶ No welding on installation
- ▶ Bushed fork positioning shoes for maximum life and smooth movement
- ▶ Adjustment for equal fork travel speed
- ▶ Drilled to suit original truck carriage – quick and easy to install
- ▶ Pressure relief to prevent clamping or sideways forces fitted on all SB models.

Options

- ▶ Different widths and opening ranges
- ▶ Different backrest sizes
- ▶ Independent fork positioning
- ▶ Different forks sizes
- ▶ Hose reels, solenoid valves and buttons for easy hydraulic installation.

Note: No relief valve fitted on SC models

	Model FLN	Capacity	Opening Range	Wt	Carriage Width	HCG	VCG	Overall Height	Max Fork Width
		kg/mm	B mm	kg	A mm	mm	mm	mm	E mm
Class 2	FLN SB2 025 092	2500/500	360 – 850	78	920	7	735	1100	127
	FLN SB2 025 102	2500/500	360 – 950	84	1020	7	740	1100	127
	FLN SB2 025 104	2500/500	360 – 970	86	1040	7	714	1100	127
	FLN SB2 025 108	2500/500	360 – 1010	83	1080	7	726	1100	127
	FLN SB2 025 115	2500/500	360 – 1080	84	1150	7	740	1100	127
Class 3	FLN SB3 035 100	5000/500	420 – 930	105	1000	3	766	1100	127
	FLN SB3 035 107	5000/500	420 – 1000	107	1070	4	805	1100	127
	FLN SB3 035 119	5000/500	420 – 1120	112	1190	5	816	1100	127
	FLN SB3 035 152	5000/500	420 – 1455	124	1525	6	838	1100	127
	FLN SB3 035 163	5000/500	420 – 1560	128	1630	6	844	1100	127
	FLN SB3 035 180	5000/500	420 – 1730	133	1800	6	849	1100	127
	FLN SB3 050 100	5000/500	420 – 930	105	1000	3	766	1100	152
	FLN SB3 050 107	5000/500	420 – 1000	107	1070	4	805	1100	152
	FLN SB3 050 119	5000/500	420 – 1120	112	1190	5	816	1100	152
	FLN SB3 050 152	5000/500	420 – 1455	124	1525	6	838	1100	152
Class 4	FLN SB3 050 163	5000/500	420 – 1560	128	1630	6	844	1100	152
	FLN SB3 050 180	5000/500	420 – 1730	133	1800	6	849	1100	152
	FLN SB4 080 119	8000/600	420 – 1100	123	1190	6	820	1100	152
	FLN SB4 080 152	8000/600	420 – 1425	136	1525	6	825	1100	152
	FLN SB4 080 180	8000/600	420 – 1700	146	1800	6	840	1100	152
	FLN SB4 080 200	8000/600	420 – 1900	154	2000	7	860	1100	152
	FLN SB4 080 240	8000/600	420 – 2300	170	2400	8	900	1100	152

Talk with your local Kaup representative about your attachment needs



SIDESHIFTING



FORK POSITIONING



CLAMPING



ROTATING / TIPPING



EXTENDING / RETRACTING



MULTI HANDLING



LIFTING



STABILISING

1800 464 712 kaup.com.au

5-11 Helium St Narangba Queensland 4504 Australia
Tel +61 7 3888 1277 Fax +61 7 3888 3838



30 years service to
the local materials
handling industry

