



Fork Positioner T466

with **independent sideshift** · without forks · for forks acc. to ISO 2330 · 2 hydraulic functions

Model	Capacity kg	LCD mm	Opening range centre to centre fork			B mm	C mm	S mm	suitable for max. fork width	ISO cl.	V mm	CofG Z mm	CofG _v Y mm	Weight kg	
			A mm	A1 mm	A2 mm										
2 T 466B	2.500	500	150-690	250-790	320-860	880	240	± 100	120	2	138	55	245	137	
			150-790	250-890	320-960	980						55	244	141	
			150-850	250-950	320-1.020	1.040						56	242	145	
			150-950	250-1.050	320-1.120	1.150						57	240	152	
			150-1.150	250-1.250	320-1.320	1.350						57	238	164	
			150-1.250	250-1.350	320-1.420	1.450						148	62	237	196
			150-1.350	250-1.450	320-1.520	1.550						64	235	203	
			150-1.450	250-1.550	320-1.620	1.650					67	232	211		
2,5 T 466B	2.500	600	150-850	250-950	320-1.020	1.040	240	± 100	120	2	153	59	227	170	
			150-950	250-1.050	320-1.120	1.150						62	229	185	
3,5 T 466B	3.500	500	180-880	250-950	320-1.020	1.040	240	± 100	130	3	153	62	283	190	
			180-980	250-1.050	320-1.120	1.150						63	282	198	
			180-1.080	250-1.150	320-1.220	1.250						63	281	206	
			180-1.180	250-1.250	320-1.320	1.350						64	280	213	
			180-1.280	250-1.350	320-1.420	1.450						64	279	221	
			180-1.380	250-1.450	320-1.520	1.550						64	278	228	
			180-1.480	250-1.550	320-1.620	1.650						65	277	236	
4,8 T 466B*	5.000	600	180-980	250-1.050	320-1.120	1.150	255	± 100	150	3	153	68	277	243	
			180-1.180	250-1.250	320-1.320	1.350						69	275	262	
			180-1.280	250-1.350	320-1.420	1.460						69	274	273	
			180-1.360	250-1.430	320-1.500	1.550						69	274	282	
			180-1.480	250-1.550	320-1.620	1.650						163	74	270	324
			180-1.580	250-1.650	320-1.720	1.750						75	270	337	
			180-1.680	250-1.750	320-1.820	1.850					75	269	350		
6 T 466	6.000	600	260-1.060	350-1.150	440-1.240	1.350	330	± 100	150	4	176	72	372	348	
			260-1.170	350-1.260	440-1.350	1.460						72	370	363	
			260-1.360	350-1.450	440-1.540	1.650			± 160			72	370	383	
			260-1.560	350-1.650	440-1.740	1.860						72	366	404	
8 T 466	8.000	600	260-1.560	350-1.650	440-1.740	1.860	330	± 160	150	4	176	72	366	404	
			260-1.760	350-1.850	440-1.940	2.060						73	364	425	
			260-1.960	350-2.050	440-2.140	2.260						73	362	445	
			260-2.060	350-2.150	440-2.240	2.400						74	359	460	
10 T 466	8.000	1.100	260-1.760	360-1.860	460-1.960	2.060	370	± 160	200	4	238	110	351	700	
			260-1.960	360-2.060	460-2.160	2.260						110	350	725	
			260-2.060	360-2.160	460-2.260	2.400						110	349	745	

*4,8T with capacity (kg/mm) 2.700/1.200 available upon request.

Not suitable for clamping between the forks.

Widths for reach trucks available upon request.

Load Backrest Model T479. Forks suitable for above attachments available upon request.